



雙片單向開重疊門自動門機組 Double-Panel One Way type AUTO DOOR



採用最新科技智慧型，
微電腦數位控制系統，
DC直流無刷馬達

The latest intelligent micro-computer
control system is adopted and
DC brushless motor.

規格性能表 Technical Specifics

項目 Items	單 門 Single Panel	雙 門 Bi Parting Panel
門重量 Door Panel Weight	150kg x 1 (片)	120kg x 2 (片)
門幅度 Operating Range	700mm~2000mm x 1 (片)	700mm~1500mm x 1 (片)
鋁合金軌道 Alum.Alloy Track Length	2500mm	4200mm
開關門速度 Open / Close Speed	220mm/s (秒)~500mm/s (秒) (可調式 Adjustable)	
使用電源 Power Supply	AC110V ± 10%, AC220V ± 10%, 50Hz ~ 60Hz,	
驅動馬達 Motor	DC24V / 70W 直流無刷馬達 Brushless Driver	
傳動馬達 Driving	馬達與齒輪比分離式組合，採用S3M齒輪時規皮帶 Setting SP-type with Motor and Tooth Pulley: Used S3M Toothed Timing Belt	
傳動皮帶 Drive Belt	S8M齒型時規皮帶 S8M Toothed Timing Belts	
調整方式 Adjustable function	按鍵式數字型視窗功能鍵 Digit Display with Numerical Keypad	
控制器 Controller	智慧型CPU微電腦數位控制全開閉監控 The CPU microcomputer several bits check the global make and break monitoring	
重量功能 Change Weight Function	分為四段指撥切換功能，備有輕型、中型、重型、加重型 4 Section Switch for Light, Moderate, Heavy, and Ultra-Heavy Duty	
開門幅度 Open Option	全開、半開、半開以上幅度無段式調整開門幅度Full and ajar. The ajar above scope does not have the section of type adjustment opening the door scope	
開門停留時間 Delay Time to Closing	1 - 99 Seconds (秒)	
防止夾人 Anti-Clamping	可調整夾人力道反轉開門 May adjust the overcrowded strength reverse to open the door	
環境溫度 Operating Temperature	-20°C~50°C	
其他 Others	安全衝擊檢知，自我故障偵測警報...等。The security impact dashes, Diagnosis Alert...etc.	

使用方法及基本動作: 電源 ON → 偵測行程 → 徐行開門 → (開門狀態) → 徐行關門 → 慢速關門 → 停車 → (關門狀態) → 檢知ON → 常速開門 → 煞車 → 慢速開門 → 停車(呈開門狀態) → 檢知OFF → 常速關門 → 煞車 → 慢速關門 → 夾合 → 停車(關門狀態)

Application method & elementary action: ON → Detect → Normal speed door open → (Door open) → Normal speed door close → Slow speed door close → Brakes → (Door close) → Detector ON → Normal speed door open → Brakes → Slow speed door open → Stop (door open) → Detector OFF → Normal speed door close → Brakes → Slow speed stop → Closing → Stop (door close)